



Residential BESS

US5000



Safety

Multi-protection from self developed BMS



Optimal Electricity Cost

Long cycle life and superior performance



Compact Size & East Installation

Module design help for quick installation



Easy to Scale Up

Be workable to be parallel based on 48V



Compatibility

Compatible with Tier 1 inverter brands

PYLON

SPECIFICATION



Module

US5000

US5000-B

Basic Parameters

Nominal Voltage (Vdc)		48	48
Nominal Capacity(Wh)		4800	4800
Depth of discharge (%)		95	95
Usable Capacity(Wh)		4560	4560
Dimension(mm)		442*420*161	442*420*161
Weight (Kg)		38	39
Discharge Voltage (V)		44.5 ~ 53.5	44.5 ~ 53.5
Charge Voltage (V)		52.5 ~ 53.5	52.5 ~ 53.5
Charge/Discharge Current (A)	Recommend	75	75
Charge/Discharge Current(A)	Max.	120@15min	120@15min
Charge/Discharge Current (A) 2	Peak 2	200@15sec	200@15sec
Communication		RS485, CAN	RS485, CAN
Configuration (max. in 1 battery group)		16pcs	16pcs
Working Temperature	Charge	0°C ~55°C	0°C ~55°C
Working Temperature	Discharge	-10°C ~55°C	-10°C ~55°C
Shelf Temperature		-20°C ~60°C	-20°C ~60°C
Short current/duration time		<4000A/2ms	<4000A/2ms
Cooling type		Natural	Natural
Breaker		No	Yes
IP rating of enclosure		IP20	IP20
Humidity		5% ~ 95%(RH) No Condensation	5% ~ 95%(RH) No Condensation
Altitude(M)		<4000	<4000
Certification		IEC / CE / UN38.3/UL	IEC / CE / UN38.3/UL
Design life		15+ Years (25°C/77°F)	15+ Years (25°C/77°F)
Cycle Life		>6,000 25°C	>6,000 25°C
Reference to standards)		IEC62619, IEC63056, CE, UN38.3, UL1973, UKCA	IEC62619, IEC63056, CE, UN38.3, UL1973, UKCA, CEC